

FASA SOUND

HOBBY HIGH PRESSURE CLEANERS > COLD WATER HIGH PRESSURE CLEANERS
NA ZEWNĄTRZ



CODE: 8.084.0010C

SOUND



FEAT URES

Three steel pistons, aluminium axial pump head with built-in by-pass valve. Automatic Stop System. Trolley with ergonomic handle. Power cable with plug
Standard equipment:Gun with quick connection. 4 m high pressure hose. Highpressure lance with Turbo fan jet lance. Foam lance + bottle

TECHNICAL CHARACTERISTICS

Pressure	110 bar max
EWbar	140 bar max
Max delivery rate	330 l/h
Absorbed power	1.5 kW
Voltage	230 V-50 Hz

STANDARD ACCESSORIES



09 c gun with quick connection
'09 c Gun with Quick coupling

Lance '02 V fan Jet ø 0.9
Launches '02 V fan Jet?
??
0.9



Foam lance + bottle
foam + jar Diffusor



H.P. 4 m hose with quick connection for S'09
A.P. 4 m Hose with quick connection for S '09



Lance with nozzle holder
Launches nozzle head port



Quick connection 3/4 F
quick-mount 3/4 F



TURBO nozzle head ø 1.025

TURBO nozzle Head
d. 1.025 (for nozzle No.
6.002.0340)

OPTIONAL



09 C GUN WITH QUICK CONNECTION AND 1/4" ADAPTER
' 09 c Gun with quick connector and 1/4 "adapter



ADJUSTABLE LANCE FOAMER/HIGH PRESSURE FOAM LANCE
adjustable nozzle/FOAMER Lance high pressure



SAND BLASTING LANCE
Sandblaster Nozzle



10 M PIPE CLEANING HOSE
10 m flusher Sensor



FIXED BRUSH
fixed Brush



QUICK COUPLING 1/4" M X M22
junction Fitting 1/4 "tubing M x M22



WATER INLET HOSE 3 M
water inlet Hose 3 m



QUICK CONNECTION 3/4 WITH BUILT-IN FILTER
quick-mount 3/4 with built-in filter



09 C GUN SET WITH QUICK COUPLING H.P. HOSE 6 M +
' 09 c gun Kit with quick coupling H.p. hose 6 m +



CURVED LANCE
Launches curve



6 M PIPE CLEANING HOSE
6 m flusher Sensor



15 M PIPE CLEANING HOSE
S < span style = "line-height: 1.45 em;"wave > 15 m flusher



ROTATING BRUSH 04
rotating Brush 04



INLET QUICK CONNECTION
rubber Holder for Quick coupling



INLET WATER FILTER 3/4F-3/4 M
suction Filter 3/4F-3/4 M



SURFER PATIO CLEANERS
Con surfer grazie all'alta pressione ed al doppio ugello rotante è possibile lavare perfettamente le superfici esterne senza fastidiosi schizzi.

Nota: da utilizzare solo ad acqua fredda